

# FBFM

The Fullbore Flowmeter, combined with our Temperature tool, will allow you to run a production profile. The FBFM features a three-arm spring-loaded cage to center the impellers across multiple casing sizes, so you only need to buy one tool. The blades' design allows the impeller to operate in small-production-rate wells, thanks to low-friction bearings and a large cross-sectional area. The tool is supplied with ancillary items that enable you to run in all casing sizes from 4-1/2" to 9-5/8".

## Features:

- Injection and production flow profiling.
- Leak detection.
- Low or high flow rates.



|                           |   |
|---------------------------|---|
| <b>Temperature rating</b> | <b>1770C (3500F)</b>                            |
| <b>Pressure rating</b>    | <b>103.4 MPa (15,000 psi)</b>                   |
| <b>Tool Diameter</b>      | <b>43mm (1-11/16")</b>                          |
| <b>Length</b>             | <b>1064mm (41.92") (Electronics + Fullbore)</b> |
| <b>Weight</b>             | <b>3.6kg (8lb)</b>                              |
| <b>Casing range</b>       | <b>4-1/2" to 9-5/8"</b>                         |
| <b>Flow output</b>        | <b>10 pulses/revs (directional)</b>             |
| <b>Threshold</b>          | <b>&lt;0.5m/min (&lt;1.6ft/min)</b>             |
| <b>Max fluid velocity</b> | <b>90Bpd</b>                                    |
| <b>Material</b>           | <b>Sour Service</b>                             |
| <b>Connector</b>          | <b>go-connector (single pin)</b>                |
| <b>Flow measure point</b> | <b>414mm (16.3")</b>                            |



For enquires please contact our distributor:  
**Flowlift Inc.**  
**105-500 29 Street SE**  
**Calgary, AB T2Z 3W9**